GREEN SLOPE

Application Instructions:

1. Open bucket and remove- Bag, brush, gloves and paper.
2. Place bag over bucket, empty contents in bag- Remove resin quart.
3. Prior to mixing, ensure surface is clean, dry and damage free. For maximum adhesion, apply 297-X Primer prior to application.
4. Once you're ready to mix, place gloves on and empty resin into bag. Use brush to remove ALL of the resin into the bag.
5. Give contents a quick mix with your hands and knead bag to combine the product thoroughly. Hint- Mix should be done within 15 mins. While kneading, allow space in bag for product to tumble.
6. Dump product into low areas and spread with trowel or tool. Compact product to provide a solid form. Scrape and compact to level or create slope.
7. Repeat for desired results.
8. Once product has dried (12-24hrs), apply 2 coats of Tucson Rubberized Coating's topcoat Premium products to ensure product longevity.

How to Video Guide



ADDITIONAL QUESTIONS? CONTACT US

(520) 293-7000

6351 S Tucson Blvd, Tucson, AZ. 85706

www.rubberized.com

TUCSON RUBBERIZED COATINGS™

570 ROOF PONDING REPAIR KIT

DESCRIPTION:

PRODUCT NO. 570 is a roof leveling compound that helps eliminate water ponding areas on flat rooftops. This product is used to fill low spots and divert standing water by creating positive slope over a variety of substrates.

SURFACE PREPARATION:

First, remove all standing water from the area and make any needed repairs to the roof. Then, sweep / blow the area to remove all dirt, ensuring a good primer bond. For extremely dirty areas, it may help to pressure wash the area with an all-purpose cleaner. Clean at least 6"-12" beyond the ponding area so your topcoat will blend with the existing roof. Once the area is completely dry and all dirt has been removed, prime the area using the enclosed pint of polyurethane-based primer/adhesive.

APPLICATION:

MIX AND SPREAD: Add the remaining primer/adhesive with the recycled EPDM granules and EPS resins to the provided mixing bag and mix thoroughly. If you do not need to use all the material, mix proportional amounts of the primer/adhesive and granules. A drill mixer can be used to speed the mixing time. Then, pour the contents out over the low area and spread the mixture using a trowel to bring the roof surface to it's original slope. Compress the material by stamping it down with a trowel to help close any open pores - especially around the perimeter to prevent water infiltration. If you keep your trowel wet with water, you can get a smoother finish.

TOP COAT: Once the material is cured, approximate dry time is 2-4 hours depending on thickness and temperature, apply a topcoat to fully waterproof the area and match the color of the existing roof. Once the area is level and a topcoat is applied, installation is complete and positive water flow to desired drainage areas can be achieved.

COMPATIBLE SUBSTRATES:

- Single Ply - EPDM, TPO, PVC
- Modified Bitumen/BUR
- Metal
- Foam
- Shingle

COMPATIBLE TOPCOATS:

- Membranes - Modified, TPO, EPDM, etc
- Coatings/Mastics (Brush or Trowel-Grade)
- Elastomerics, Silicones, Asphalt Emulsions, Roof Granules, Roof Cements

**It is best to use low solvent products.*

STORAGE:

Store in tightly closed containers in a cool, dry and well-ventilated area away from heat or sources of ignition. Keep out of direct sunlight. Store in temperatures 40°F (4.4°C) minimum to 90°F (32.2 ° C) maximum. Product performance, as a result of proper storage, is guaranteed six months from the date shipped from the manufacturer.

CLEAN-UP:

Clean brushes, tools and other equipment with warm soapy water immediately after use. Dried film may require paint remover.

KIT INCLUDES:

- Recycled EPDM Granules & EPS Resins
- Greenslope Primer/Adhesive
- Mixing Bag
- 3" Brush
- Rubber Gloves

WARNING:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause damage to respiratory system through prolonged or repeated exposure.

PRECAUTIONS:

Do not breathe mist, vapors or spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

EXTINGUISHING MEDIA:

CO2, sand, extinguishing powder. Do not use extinguishing media containing water.

CALIFORNIA PROPOSITION 65:

This product contains no chemicals known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

HANDLING PRECAUTIONS:

Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use, physical and health hazard information. Safety data sheets are available on the TRC website at www.rubberized.com. You can also obtain a copy from one of our local TRC stores.

LIMITED WARRANTY AND DISCLAIMER:

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact TRC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with TRC warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: www.rubberized.com.

©2023 Tucson Rubberized Coatings
Manufactured by Tucson Rubberized Coatings
6351 S. Tucson Blvd. Tucson, AZ 85706